

Compact Grinder

TROCKENSCHLIFF

DRY GRINDING



Arbeitsbreite 150mm
Working width 150mm

- ✓ **Finishing**
- ✓ **Schleifen - Grinding**
- ✓ **Entgraten - Deburring**



C-150 2K/B

Compact Grinder

VBM
Briekrode GmbH

TROCKENSCHLIFF DRY GRINDING



Schleibänder
Grinding belts



Vliesbänder
Scotch belts



Vliesbürsten
Scotch brushes



R



2R



3R



4R

Aggregate 1-4
Bürsten | Brushes 1-2



Superfinish

www.vbm-germany.com

Compact Grinder C-150

Technische Daten / technical data					
Modelle Model	Schleifaggr. Grinding belt	Bürstagr. Brush unit	Staubausgang Dust connection	Abmessungen LBH Dimension LWH	Gewicht Weight
C-150 K	1 x 3 KW	-	Ø 1 x 100mm	1,4 x 0,9 x 1,9m	400 KG
C-150 K/B	1 x 3 KW	1 x 3 KW	Ø 2 x 100mm	1,4 x 0,9 x 1,9m	480 KG
C-150 K/2B	1 x 3 KW	2 x 3 KW	Ø 3 x 100mm	1,4 x 0,9 x 1,9m	650 KG
C-150 2K	2 x 3 KW	-	Ø 2 x 100mm	1,4 x 0,9 x 1,9m	520 KG
C-150 2K/B	2 x 3 KW	1 x 3 KW	Ø 3 x 100mm	2,3 x 0,9 x 1,9m	730 KG
C-150 2K/2B	2 x 3 KW	2 x 3 KW	Ø 4 x 100mm	2,3 x 0,9 x 1,9m	760 KG
C-150 3K	3 x 3 KW	-	Ø 3 x 100mm	2,3 x 0,9 x 1,9m	720 KG
C-150 3K/B	3 x 3 KW	1 x 3 KW	Ø 4 x 100mm	2,3 x 0,9 x 1,9m	800 KG
C-150 4K	4 x 3 KW	-	Ø 4 x 100mm	2,3 x 0,9 x 1,9m	840 KG
Schleifband LxB / Grinding belt LxW		1900 x 150 mm			
Bürste ØxB / Brush ØxW		Ø 200 x 150 mm			
Arbeitshöhe / working high		konstant / constant H= 830 mm			
Kontaktwalze / Contact drum		Ø 122, 35°/70° SH			
Schleifbandspannung / Belt tension		mechanisch / mechanical			
Arbeitsdicke / working thickness		0,5 - 200 mm (0,1mm Einstellung/Adjustment)			



VBM Brinkrode GmbH
 Rubensweg 5
 D-59302 Oelde / Germany
 Tel: +49-2522-901 707
 Fax: +49-1805-060 337 033 92
 E-Mail: info@vbm-germany.com
 Web: www.vbm-germany.com

Superfinish
www.vbm-germany.com